

COMPUTATION OF EFFECTIVE DEBYE TEMPERATURE (θ_D) OF BINARY LIQUID MIXTURES

Satendra Singh¹, Aruna Singh¹ and Shailendra Badal^{2*}

¹Department of Chemistry, K.N.Government P.G. College, Gyanpur, Bhadohi, Uttar Pradesh, India.

²Department of Chemistry, Hindustan College of Science and Technology, Farah, Mathura, Uttar Pradesh, India.

ABSTRACT

On the basis of quasicrystalline model of liquid state effective Debye temperature (θ_D), of 32 binary liquid mixtures at 298.15 K has been computed using sound velocity and density data, mixtures under the present investigation contain benzene, toluene, p-xylene, 1-chloronaphthlene and 1-chlorobenzene with n- and br- alkanes. θ_D values of all the mixture were also calculated on the basis of Lorenz - Bertholet combination rule using heat capacity data. The results are found to be quite satisfactory which are discussed critically.

Keywords: Debye temperature, binary liquid mixtures, n- and br-alkanes, sound velocity.

INTRODUCTION

During the period 1974-1976, a number of workers¹⁻⁸ evaluated the effective Debye temperature of pure liquids as a fraction of temperature and pressure on the basis of quasicrystalline behavior and other experimental evidence. The approach utilized the experimental data of density, ultrasonic velocity and absorption of liquids. Subsequently the traditional method, having several approximations and limitations, was modified and extruded to binary⁹ and multicomponent liquid mixture¹⁰ for the computation of effective Debye temperature. Recently¹¹ an independent method for computing the specific heat ratio, Gruneisen parameter and Debye temperature of crude oil has been developed. Due to increasing importance of Debye temperature of liquids, we are reporting here the results of calculation of θ_D for several binary liquid mixtures.

For the present work we have taken 32 binary liquid mixtures of benzene, toluene, p-xylene, 1-chloronaphthlene and 1-chlorobenzene with n- and br- alkanes, all at 298.15 K. The experimental data of density, sound velocity, heat capacity, isothermal compressibility and thermal expansivity were taken from the literature.¹²⁻¹³

FORMULA USED

The basic equation employed for the calculation of the effective Debye temperature are, θ_D , can be written as

$$\theta_D = \frac{h}{k} \left[\frac{\left(\frac{9N}{4\pi V} \right)}{\left(\frac{1}{C_l^3} + \frac{2}{C_t^3} \right)} \right] \dots\dots\dots (1)$$

Where all the symbols have their usual notations as given in earlier papers.¹⁴ Without going into further details it can be shown that the resulting expression for computing θ_D

$$\theta_D = \left[\frac{9N/4\pi V}{(\rho\beta_a)^{3/2} \left\{ \left(\frac{1}{1+\gamma} \right)^{3/2} + 2 \left(\frac{4}{3\gamma} \right)^{3/2} \right\}} \right]^{1/3} \dots\dots\dots (2)$$

Where, $\gamma = \frac{C_P}{C_V} = \frac{\beta_T}{\beta_S}$

$\beta_a = (\rho u^2)^{-1}$

ρ and u being the density and isentropic compressibility of liquid mixture. Now we are introducing two different methods for obtaining the value of Debye temperature of a liquid mixture.

1. Ideal mixture relation.

$$\theta_D = \sum X_i \theta_{Di} \dots\dots\dots (3)$$

Where,

X_i is the mole fraction of i^{th} component and θ_{Di} the Debye temperature of i^{th} component.

2. According to Lorenz – Bertholet combination rule,

$$m_1 s_1 (t_1 - t) = m_2 s_2 (t - t_2) \dots\dots\dots(4)$$

Where m , s and t are the mass specific heat and temperature respectively. If we use the mole fraction, molar heat capacity and Debye temperature in place of mass, specific heat and temperature in equation (4), it becomes,

$$\begin{aligned} X_1 C_{P1} (\theta_{D1} - \theta_D) &= X_2 C_{P2} (\theta_D - \theta_{D2}) \\ X_1 C_{P1} \theta_{D1} - X_1 C_{P1} \theta_D &= X_2 C_{P2} \theta_D - X_2 C_{P2} \theta_{D2} \\ \theta_D (X_1 C_{P1} - X_2 C_{P2}) &= X_1 C_{P1} \theta_{D1} + X_2 C_{P2} \theta_{D2} \\ \theta_D &= \frac{X_1 C_{P1} \theta_{D1} + X_2 C_{P2} \theta_{D2}}{X_1 C_{P1} + X_2 C_{P2}} \\ \theta_D &= \frac{\sum X_i C_{Pi} \theta_{Di}}{\sum X_i C_{Pi}} \dots\dots\dots (5) \end{aligned}$$

Where C_{pi} is the molar specific heat capacity at pressure of i^{th} component. Using these methods we have calculated the Debye temperature of mixture and compared with the standered values obtained with the help of equation (2).

The Debye frequency ν_m , was obtained from the equation

$$\nu_m = \frac{k}{h} \times \theta_D \dots\dots\dots (6)$$

RESULT AND DISCUSSION

For the computation of effective Debye temperature θ_D and Debye frequency ν_m of 32 equimolar binary mixtures of benzene, toluene, p-xylene, 1-chloronaphthlene and 1-chlorobenzene with normal and branched alkanes, at 298.15 K. The experimental data of density (ρ), sound velocity (u), adiabatic compressibility (β_s) and thermal expansivity (α) were taken from literature.¹²⁻¹³

Equations (2-5,6) were used to obtain the values of θ_D and ν_m for all the liquid mixtures. These values are reported in Tables -1,2,3,4 and 5 respectively for the mixtures benzene +n-C₆, +n-C₈, +n-C₁₀, +n-C₁₂, +n-C₁₆; toluene +n-C₆, +n-C₈, +n-C₁₀, +n-C₁₂ and br-C₁₂; p-xylene +n-C₆, +n-C₁₆; 1-chloronaphthlene +n-C₆ to +n-C₁₆, +br-C₆ to br-C₁₆; and 1-chlorobenzene +n-C₆ to +n-C₁₆, +br-C₆ to br-C₁₆.

A perusal of results reported in Tables 1-5 show that the calculated values of θ_D and ν_m in all system decrease with the number of carbon atom from C₆ to C₁₆. Similar trend is also observed in case of ν_m . The role of common liquids benzene, toluene, p-xylene, 1-chloronaphthlene and 1-chlorobenzene in all the mixture is not significant towards the change in the value of θ_D and ν_m . Increase in C- atoms of alkanes results in the attaining the more crystalline character of liquids that reduce the θ_D values.

Table 1: Calculated values of the effective Debye temperature (θ_D) and Debye frequency of benzene with n-alkane at 298.15 K

Liquids	X ₁	T(°K)	ρ (kgm ⁻³)	u (ms ⁻¹)	θ_D (°K)	ν_m (10 ⁹)
Benzene with						
n-C ₆	0.50	298.15	687.15	1155.56	116.76	5.61
n-C ₈	0.50	298.15	687.15	1201.71	115.99	5.57
n-C ₁₀	0.50	298.15	687.15	1236.20	114.61	5.50
n-C ₁₂	0.50	298.15	687.15	1263.15	110.53	5.42
n-C ₁₆	0.50	298.15	687.15	1305.30	109.67	5.26

Table 2: Calculated values of the effective Debye temperature (θ_D) and Debye frequency of toluene with n-alkane at 298.15 K

Liquids	X ₁	T(°K)	ρ (kgm ⁻³)	u (ms ⁻¹)	θ_D (°K)	ν_m (10 ⁹)
Toluene with						
n-C ₆	0.50	298.15	687.9	1177.67	116.16	5.58
n-C ₈	0.50	298.15	687.9	1214.59	114.80	5.51
n-C ₁₀	0.50	298.15	687.9	1250.97	113.84	5.47
n-C ₁₂	0.50	298.15	687.9	1273.83	112.02	5.38
n-C ₁₆	0.50	298.15	687.9	1316.79	109.12	5.24

Table 3: Calculated values of the effective Debye temperature (θ_D) and Debye frequency of p-xylene with n-alkane at 298.15 K

Liquids	X ₁	T(°K)	ρ (kgm ⁻³)	u (ms ⁻¹)	θ_D (°K)	ν_m (10 ⁹)
p-xylene with						
n-C ₆	0.50	298.15	687.9	1186.51	114.43	5.49
n-C ₁₆	0.50	298.15	687.9	1321.08	108.02	5.19

Table 4: Calculated values of the effective Debye temperature (θ_D) and Debye frequency of 1-chloronaphthalene with n-alkane at 298.15 K

Liquids	X_1	T(°K)	ρ (kgm ⁻³)	u (ms ⁻¹)	θ_D (°K)	ν_m (10 ⁹)
1-chloronaphthalene with						
n-C ₆	0.50	298.15	687.9	1266.97	120.60	5.79
n-C ₈	0.50	298.15	687.9	1298.18	118.84	5.71
n-C ₁₀	0.50	298.15	687.9	1320.93	116.72	5.62
n-C ₁₂	0.50	298.15	687.9	1338.68	114.65	5.50
n-C ₁₄	0.50	298.15	687.9	1357.10	112.92	5.42
n-C ₁₆	0.50	298.15	687.9	1373.59	111.30	5.34
br-C ₆	0.50	298.15	687.9	1224.32	116.28	5.58
br-C ₈	0.50	298.15	687.9	1252.78	114.43	5.49
br-C ₁₂	0.50	298.15	687.9	1287.98	110.22	5.29
br-C ₁₆	0.50	298.15	687.9	1324.46	107.65	5.17

Table 5: Calculated values of the effective Debye temperature (θ_D) and Debye frequency of 1-chlorobenzene with n-alkane at 298.15 K

Liquids	X_1	T(°K)	ρ (kgm ⁻³)	u (ms ⁻¹)	θ_D (°K)	ν_m (10 ⁹)
1-chlorobenzene with						
n-C ₆	0.50	298.15	850	1158.43	93.2	4.47
n-C ₈	0.50	298.15	850	1200.37	92.43	4.44
n-C ₁₀	0.50	298.15	850	1232.41	91.27	4.38
n-C ₁₂	0.50	298.15	850	1260.28	90.15	4.33
n-C ₁₄	0.50	298.15	850	1200.89	83.23	4.00
n-C ₁₆	0.50	298.15	850	1303.70	87.7	4.22
br-C ₆	0.50	298.15	850	1118.72	89.78	4.31
br-C ₈	0.50	298.15	850	1151.69	88.46	4.25
br-C ₁₂	0.50	298.15	850	1206.74	86.26	4.14
br-C ₁₆	0.50	298.15	850	1259.15	84.13	4.04

REFERENCES

- Pandey JD and Pandey HD. Effective Debye temperature of and specific heat ratio in liquid methane and pentane. Indian J Phys. 1975;49:869-872.
- Pandey JD. Acoustical parameters of liquid fluorine, Acustica. 1975;34:119-120.
- Pandey JD and Pandey HC. The study of effective Debye temperature of liquid Ar. Acustica. 1976; 34:243-245.
- Pandey JD and Pant UR and Bhatt T. Acoustical behavior of liquid diborane. Acustica. 1976;34: 247-249.
- Pandey JD. Acoustical behavior of plastic crystals. Acustica. 1976;35:87-88.
- Jain SC and Bhandari RC. On the Debye temperature of light and heavy water. J Phys Soc Japan. 1967;23:476-477.
- Saxana NS and Bhandari RC. Debye temperature of liquid metals. Ind J Pure Appl Phys. 1975;13: 270-271.
- Kor SK and Tripathi ND. Temperature and pressure dependence of effective Debye temperature in associated liquids based on quasi crystalline model. J Phys Soc Japan. 1974;36:552-554.
- Pandey JD. Ultrasonic propagation parameters and the effective Debye temperature in liquid mixtures, Acoustic Letters. 1979;3:90-94.
- Pandey JD, Sanguri V, Mishra RK and Sing AK. Acoustic method for the estimation of effective Debye temperature of binary and ternary liquid mixtures. J Pure Appl Ultrason. 2004;26:18-29.
- Singh RN, George AK and Arafin S. Specific heat ratio, Gruneisen parameter and Debye temperature of crude oil. J Phys D Appl Phys. 2006;39:1220-1225.
- Tardajos G, Aicart E, Costas M and Patterson D. Liquid structure and second-order mixing functions for benzene, toluene and p-xylene with n-alkanes. J Chem Soc. Faraday Trans I. 1986;82: 2977-2987.
- Patterson D, Tra HV, Costas M, Trejo LM, Perez-Casas S, Aicart E, Tardajos G and Dominiguez A. Van der waals liquids, Flory Theory and mixing functions for chlorobenzene with linear and branched alkanes. J Chem Soc Faraday Trans. 1993;89:89-93.
- Pandey JD, Singh AK and Dey A. Effect of isotopy on thermoacoustical properties. Ind J Pure Appl Ultrason. 2004;26:100-104.